# **Self-Aligning Pads** • adjustable, self-resetting 22741.0016



# **Product Description**

Self-aligning pads are used as stop, support and thrust pad and are suitable for installation in clamping elements.

By resetting to the parallel position the contact point of the self-aligning pad provides a defined initial position, thus preventing the pad clamping in an oblique position when inserting the workpiece.

## **Material**

# Spring element

· Thermoplastic PUR

· Ball-bearing steel, hardened, bright

## **Body**

· Heat-treated steel, tempered, phosphated

• Steel, blackened (ISO 4035)


# More information


#### **Notes**

Ball protected against rotating. Loading capacity valid for steel and stainless steel designs.


Customized design on request.

# **Drawing**





Erwin Halder KG



picture 1

picture 2

# **Order information**

Dimensions						Load capacity	Tightening torque	I	Art. No.
d <sub>1</sub>	I	l <sub>1</sub>	d <sub>2</sub>	е	Ball diameter	for static load	max.		
						max.			
[mm]						[kN]	[Nm]	[9]	
with flat-faced ball, bearing surface plain – picture 1, Heat-treated steel									
M10	45.7	30	8.6	19	12	8	46	44	22741.0016

www.halder.com Page 1 of 2

Published on: 13.11.2024

# Compliance

# **RoHS** compliant

Compliant according to Directive 2011/65/EU and Directive 2015/863.

# Does not contain SVHC substances

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 27.06.2024.

# Does not contain Proposition 65 substances

No Proposition 65 substances included. https://www.P65Warnings.ca.gov/

# **Free from Conflict Minerals**

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



Page 2 of 2 Published on: 13.11.2024

www.halder.com