# Index Bolts • with mounting flange, horizontal 22120.1224



## **Product Description**

Index bolts are used for indexing purposes.

#### **Material**

# Housing

· Zinc die-cast, plastic coated, black

#### Locking pin

• Steel, zinc-plated by galvanization

# Catch

plastic


#### Assembly

Assembly by means of washers ISO 7092.

## Operation

When using the model with locking mechanism, you pull out the bolt, turn it by 70° and secure it using the notched catch (if the locking pin should not overhang).

Drawing




### **Order information**

	Dimensions														Spring load <sup>1)</sup>		ß		Ĩ	Art. No.
<b>d</b> -0.05	l₂ i min.	b <sub>1</sub>	b <sub>2</sub>	b <sub>3</sub>	b4	h₁	h <sub>2</sub>	h <sub>3</sub>	k <sub>1</sub>	k <sub>2</sub>	k <sub>3</sub>	k4	l <sub>1</sub>	I <sub>3</sub>	~   -	<b>-</b> ₂ ~	min.	max.	[4]	
with	[mm] [N] [°C] [g] with locking, right – picture 3																			
8	12	46	40	20	6.4	11	6	29	33	6.5	14.5	19	71	17	25 3	38	-30	80	130	22120.1224

1) statistical average value

# **Application example**



# Compliance

#### **RoHS compliant**

Contains lead - compliant according to exceptions 6a / 6b / 6c.

Contains SVHC substances >0,1% w/w Contains lead - SVHC list [REACH] as of 27.06.2024.

#### **Contains Proposition 65 substances**



Lead can cause cancer and reproductive harm from exposure https://www.P65Warnings.ca.gov/

#### **Free from Conflict Minerals**

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.