# **Mounting Pads** • protected against slipping 22590.1124



#### **Product Description**

Mounting pads can be used as foot or thrust pad. Not parallel bearing surfaces up to 15° degrees can be compensated.

The plastic cover on the mounting pad prevents slipping.

# Material

### Ball element

Stainless steel 1.4305

# Rubber capRubber, black

# Pad


• Thermoplastic POM, white


#### More information

#### Notes

For the versions  $d_1 = M10$  and M12 the lock nut conforms to DIN 934.

#### Drawing





#### **Order information**

Dimensions   d1 d2 h1 h2 t   ~ ~ ~					WS	Load capacity for static load max.	Ť.	Art. No.
[mm]					[mm]	[kN]	[g]	
pad from thermoplastic, ball element from stainless steel – picture 1, Thermoplastic								
M24	69	55	24	19	36	25	240	22590.1124

#### Compliance

#### **RoHS compliant**

Compliant according to Directive 2011/65/EU and Directive 2015/863.

## Does not contain SVHC substances

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 27.06.2024.

#### Does not contain Proposition 65 substances

No Proposition 65 substances included. https://www.P65Warnings.ca.gov/

#### Free from Conflict Minerals

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.