Self-Aligning Pads • adjustable, self-resetting 22741.0030



Product Description

Self-aligning pads are used as stop, support and thrust pad and are suitable for installation in clamping elements.

By resetting to the parallel position the contact point of the self-aligning pad provides a defined initial position, thus preventing the pad clamping in an oblique position when inserting the workpiece.

Material

Spring element

Thermoplastic PUR

· Ball-bearing steel, hardened, bright

Body

· Heat-treated steel, tempered, phosphated

• Steel, blackened (ISO 4035)


More information


Notes

Ball protected against rotating. Loading capacity valid for steel and stainless steel designs.


Special types on request.

Drawing





Erwin Halder KG



picture 1

picture 2

Order information

Dimensions						Load capacity	Tightening torque	I	Art. No.
d ₁	ı	l ₁	d ₂	е	Ball diameter	for static load	max.	_	
						max.			
[mm]						[kN]	[Nm]	[g]	
with flat-faced ball, bearing surface plain – picture 1, Heat-treated steel									
M20	77.3	50	20	33	25	90	407	273	22741.0030

www.halder.com Page 1 of 2

Published on: 10.8.2024

Compliance

RoHS compliant

Compliant according to Directive 2011/65/EU and Directive 2015/863.

Does not contain SVHC substances

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 27.06.2024.

Does not contain Proposition 65 substances

No Proposition 65 substances included. https://www.P65Warnings.ca.gov/

Free from Conflict Minerals

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



Erwin Halder KG

www.halder.com Page 2 of 2 Published on: 10.8.2024