# Adjustable Tension Levers



# **Product Description**

## **Material**

## Lever

Stainless steel 1.4305, dull blasted

## Inner parts

Stainless steel 1.4305, dull blasted

#### Ball knob

Thermosetting plastic PF 31, black, DIN 319

# Operation

**By lifting the lever** the serrations are disengaged. The lever can be positioned by the serrations. On releasing the lever, the serrations are automatically re-engaged.

#### More information


#### Notes


d<sub>2</sub>

picture 2

The threaded portion can be exchanged.

# Drawing





Order information

Dimensions										<b>I</b>	Art. No.
d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d₄	d <sub>5</sub>	h <sub>1</sub>	h <sub>2</sub>	h <sub>3</sub>	 ~	t min.	-	
[mm]										[g]	
with female thread – picture 1, Stainless steel											
28	M12	19	12	30	48.5	4.5	4.5	110	17	248	24440.0622

## Compliance

## **RoHS compliant**

Compliant according to Directive 2011/65/EU and Directive 2015/863.

## Does not contain SVHC substances

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 27.06.2024.

## Does not contain Proposition 65 substances

No Proposition 65 substances included. https://www.P65Warnings.ca.gov/

#### **Free from Conflict Minerals**

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.