# **Adjustable Tension Levers**

## 24440.0748



## **Product Description**

### **Material**

#### Lever

· Stainless steel 1.4305, dull blasted

#### Screv

• Stainless steel 1.4305

#### Ball knob

• Thermosetting plastic PF 31, black, DIN 319

### **Operation**


By lifting the lever the serrations are disengaged. The lever can be positioned by the serrations. On releasing the lever, the serrations are automatically re-engaged.


### More information


#### Notes

The threaded portion can be exchanged.

### **Drawing**







### **Order information**

Dimensions										I	Art. No.
d₁	d <sub>2</sub>	I <sub>1</sub>	d <sub>3</sub>	d₄	d <sub>5</sub>	h <sub>1</sub>	h <sub>2</sub>	h <sub>3</sub>	1	_	
[mm]											
with screw – picture 2, Stainless steel											
28	M12	50	19	12	30	48.5	4.5	4.5	110	302	24440.0748

## Compliance

### **RoHS** compliant

Compliant according to Directive 2011/65/EU and Directive 2015/863.

### Does not contain SVHC substances

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 27.06.2024.

Erwin Halder KG

## Does not contain Proposition 65 substances

No Proposition 65 substances included. https://www.P65Warnings.ca.gov/

### **Free from Conflict Minerals**

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



www.halder.com Page 1 of 1

Published on: 10.8.2024