# **Knurled Nuts • DIN 6303**

24480.0012



## **Product Description**

### **Material**

· Free cutting steel, blackened

### **Assembly**


Form B: after being bored through the pin hole is to be situated within the tolerance field H7.


#### More information

#### **Notes**

Knurling pitch and knurling depth may differ from DIN.

# Drawing





picture 1


picture 2

Erwin Halder KG

## **Order information**

Dimensions							1	Art. No.
d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d₄	h	k	t	_	
	[9]							
without pin hole, form A – picture 1, Free cutting steel								
M12	40	32	34	24	16	10	123	24480.0012

## **Application example**



Page 1 of 2 www.halder.com Published on: 10.8.2024

## Compliance

# RoHS compliant

Contains lead - compliant according to exceptions 6a / 6b / 6c.

### Contains SVHC substances >0,1% w/w

Contains lead - SVHC list [REACH] as of 27.06.2024.

#### **Contains Proposition 65 substances**



Lead can cause cancer and reproductive harm from exposure https://www.P65Warnings.ca.gov/

#### **Free from Conflict Minerals**

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



Erwin Halder KG

Page 2 of 2 www.halder.com

Published on: 10.8.2024