

## SUPERCRAFT soft-face mallets · with vibration-reducing, ergonomic and varnished Hickory handle EH 3366.



### Product Description

The tubular head of the SUPERCRAFT soft-face mallets is filled with steel shot. The resulting effect is that the energy of the steel shot is transferred with a slight delay when the mallet's contact surface hits the workpiece. The reduced rebound allows the impact energy to be absorbed with perfect efficiency. The result is impact of exceptional magnitude. What is more, SUPERCRAFT soft-face mallets allow for work with greatly improved safety, reduced strain on the joints and greater noise-dampening when compared to ordinary steel mallets.

The inserts offer outstanding impact qualities and are guaranteed to combine maximum strength with unique durability. They consist of extruded and extremely homogeneous material. Compared to injection moulded plastic inserts, they are therefore considerably more wear-resistant and durable and will never chip even in sub-zero temperatures.

The ergonomically shaped, varnished and ultra stable hickory handle has a vibration-dampening effect.

The handle protection sleeve acts as an overstrike protector. A secure handle-head connection is ensured by an aluminium wedge and a safety pin. All weld seams are completely robot-welded. Extremely tight and of premium quality, a welded connection between impact plate and hammer head keeps the steel shot filling from escaping even under maximum load. The wear-resistant power coating prevents corrosion.

Handle and inserts are replaceable.

This version is available in sizes ranging from D20mm to D80mm and as a sledge hammer weighing up to 9,300g.

#### Product features:

- Non-rebound, for extra powerful strikes.
- Noise-dampening and gentle on the joints.
- Inserts made of special nylon with maximum strength.
- Completely robot-welded.
- Vibration-dampening, ergonomically shaped, very stable and varnished hickory handle.
- Handle protection sleeve acts as an overstrike protector.
- Handle and inserts replaceable.
- Available in sizes ranging from D20mm to D80mm and as a sledge hammer weighing up to 9,300g.

### Application Areas

Positioning and joining of workpieces in the vice sheet-metal forming, assembly of sharp-edged workpieces, assembly and repair work in the automotive and truck sector, scaffold construction, straightening work, housing assembly, plant construction, maintenance work, driving in cord irons / metal stakes, for work with great power, prying work, upholsterer/saddler, hole punching with hole punches, driving eyelets with eyelet punches, driving in cramps

### Material

#### Handle

- Hickory

#### Inserts

- Nylon, white
- hard
- Very wear-resistant
- no chipping (even at temperatures below zero)
- noise-dampening
- very high impact

### Order information

Ø	Dimensions		Length x Width x Height [mm]	[g]	GTIN	proficl@ss 5.0	ecl@ss 10.1	Art. No.
20	105	300	300 x 105 x 20	245	4030618301578	AAA905c002	21-04-09-16	<a href="#">3366.020</a>
25	105	305	305 x 105 x 27	325	4030618301585	AAA905c002	21-04-09-16	<a href="#">3366.025</a>
30	110	330	330 x 110 x 32	460	4030618301592	AAA905c002	21-04-09-16	<a href="#">3366.030</a>
35	110	335	335 x 110 x 37	560	4030618301608	AAA905c002	21-04-09-16	<a href="#">3366.035</a>
40	115	355	355 x 115 x 42	715	4030618301615	AAA905c002	21-04-09-16	<a href="#">3366.040</a>
45	120	360	360 x 120 x 46	830	4030618301622	AAA905c002	21-04-09-16	<a href="#">3366.045</a>

Ø	Dimensions		Length x Width x Height [mm]	[g]	GTIN	profiel@ss 5.0	ecl@ss 10.1	Art. No.
50	120	365	365 x 120 x 53	990	4030618301639	AAA905c002	21-04-09-16	<a href="#">3366.050</a>
60	145	360	360 x 145 x 60	1705	4030618301646	AAA905c002	21-04-09-16	<a href="#">3366.060</a>
70	150	370	370 x 150 x 70	2215	4030618301653	AAA905c002	21-04-09-16	<a href="#">3366.070</a>
80	168	380	380 x 168 x 80	3210	4030618301660	AAA905c002	21-04-09-16	<a href="#">3366.080</a>

Application example





















## Compliance

For detailed compliance information please select the desired article number.